

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0

Page 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Engine Oil 0W-40
Article number: 30 10 1140, 30 10 1141, 30 10 1142, 30 10 1143, 30 10 1144

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information

info@swag.de

Safety Data Sheet

info@swag.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.

2.2 Label elements

Hazard pictograms

The product is required to be labelled in accordance with regulation CLP.



Signal word

WARNING

Contains:

C14-16-18 Alkyl phenol

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P501 Dispose of contents/container in accordance with local/national regulation.

2.3 Other hazards

Human health dangers

Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards

Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - <60	Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract) CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX GHS/CLP: Asp. Tox. 1: H304
15 - <30	1-Dodecene, polymer with 1-decene, hydrogenated CAS: 151006-60-9, EINECS/ELINCS: 604-767-8, Reg-No.: 01-2119523580-47-XXXX GHS/CLP: Asp. Tox. 1: H304
15 - <30	Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated CAS: 163149-28-8, EINECS/ELINCS: 605-315-2, Reg-No.: 01-2119543695-30-XXXX GHS/CLP: Asp. Tox. 1: H304
15 - <30	1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated CAS: 68649-12-7, EINECS/ELINCS: 614-695-9 GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	C14-16-18 Alkyl phenol CAS: 1190625-94-5, EINECS/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX GHS/CLP: Skin Sens. 1B: H317 - STOT RE 2: H373
1 - < 2,5	Bis(nonylphenyl)amine CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX GHS/CLP: Aquatic Chronic 4: H413
1 - < 2,5	Paraffin oils (petroleum), catalytic dewaxed heavy CAS: 64742-70-7, EINECS/ELINCS: 265-174-4, EU-INDEX: 649-477-00-2, Reg-No.: 01-2119487080-42-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt) CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract) CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) CAS: 93819-94-4, EINECS/ELINCS: 298-577-9, Reg-No.: 01-2119543726-33-XXXX GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411 SCL [%]: >6,25 - 100: Skin Irrit. 2: H315, >10 - 12,5: Eye Irrit. 2: H319, > 12,5: Eye Dam. 1: H318

Comment on component parts

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Consult a doctor immediately.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide
Extinguishing media that must not be used	Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0

Page 4 / 15

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX
Long-term exposure: 1200 mg/m ³

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
Industrial, dermal, Long-term - systemic effects, 5 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 2,5 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1,19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
Industrial, inhalative, Long-term - systemic effects, 8,31 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0,58 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 2,11 mg/m ³
general population, dermal, Long-term - systemic effects, 0,29 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,24 mg/kg bw/day
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
Industrial, inhalative, Long-term - systemic effects, 1,17 mg/m ³
Industrial, dermal, Long-term - systemic effects, 300 µg/kg bw/d
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1,19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day

PNEC

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
freshwater, 412 µg/L
seawater, 41.2 µg/L
sediment (freshwater), 1 mg/kg sediment dw
sediment (seawater), 0.1 mg/kg sediment dw
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
oral (food), 9,33 mg/kg food
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
freshwater, 0,004 mg/l
seawater, 0,004 mg/l
sewage treatment plants (STP), 100 mg/l
sediment (freshwater), 0,012 mg/kg dw
sediment (seawater), 0,001 mg/kg dw
soil, 0,005 mg/kg
oral (food), 10,67 mg/kg
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
freshwater, 100 µg/l
seawater, 10 µg/l
sewage treatment plants (STP), 100 mg/l
sediment (freshwater), 4266,16 mg/kg dw
sediment (seawater), 426,62 mg/kg dw
soil, 852,58 mg/kg dw
oral (food), 3,3 mg/kg
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
oral (food), 9.33 mg/kg food

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	If there is a risk of splashing: safety glasses (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. >0,4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Protective clothing (EN 340)
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	light brown
Odor	characteristic
Odour threshold	not relevant
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	236
Flammability	not flammable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm ³]	0,84 (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	>20,5 mm ² /s (40° C) 14,2 mm ² /s (100°C) (DIN 51562/T1)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

Pour point: -36°C

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
LD50, oral, Rat, 5000 mg/kg bw
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, oral, Rat, > 5000 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)
NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LD50, oral, Rat, 2600 mg/kg
NOAEL, oral, Rat, 160 mg/kg bw/day
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LD50, oral, Rat, >2000 mg/kg bw
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LD50, oral, Rat, >5000 mg/kg bw
LOAEL, oral, Rat, 125 mg/kg bw/day
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated, CAS: 163149-28-8
LD50, oral, Rat, 2000 - 5000 mg/kg bw
1-Dodecene, polymer with 1-decene, hydrogenated, CAS: 151006-60-9
LD50, oral, Rat, 2000 - 5000 mg/kg bw

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, dermal, Rabbit, > 5000 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 403)
NOAEL, dermal, Rat, >2000 mg/kg bw (OECD 414)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LD50, dermal, Rabbit, >3160 mg/kg bw/day
LOAEL, dermal, Rabbit, 70 mg/kg bw/day
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LD50, dermal, Rat, >2000 mg/kg bw
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LD10, dermal, Rabbit, >2000 mg/kg bw
NOAEL, dermal, Rabbit, >1000 mg/kg bw/day
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated, CAS: 163149-28-8
LD50, dermal, Rat, >2000 mg/kg bw
1-Dodecene, polymer with 1-decene, hydrogenated, CAS: 151006-60-9
LD50, dermal, Rat, >2000 mg/kg bw

Acute inhalational toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalation (vapour), >20 mg/L
Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air, 4h
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LC50, inhalative, Rat, >5,53 mg/l air (OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LC50, inhalative, Rat, >2 mg/l
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LC50, inhalative, Rat, 18 - 5.53 mg/L air, 4h
NOAEC, inhalative, Rat, 980 mg/m ³ air
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated, CAS: 163149-28-8
LC50, inhalative, Rat, 900 - 5200 mg/m ³ air, 4h
1-Dodecene, polymer with 1-decene, hydrogenated, CAS: 151006-60-9
LC50, inhalative, Rat, 900 - 5200 mg/m ³ air, 4h

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Eye, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
Eye, non-irritating

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
dermal, non-irritating

Respiratory or skin sensitisation May cause an allergic skin reaction.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-sensitizing
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3
NOEL, oral, Rat, 100 mg/kg bw/day
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEL, dermal, Rabbit, 1000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEC, inhalative, Rat, 980 mg/m ³ , no adverse effect observed
LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m ³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
NOAEL, oral, Rat, 100 mg/kg bw/day
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated, CAS: 163149-28-8
NOAEL, oral, Rat, 1 000 - 6771 mg/kg bw/day
1-Dodecene, polymer with 1-decene, hydrogenated, CAS: 151006-60-9
NOAEL, oral, Rat, 1 000 - 6771 mg/kg bw/day
NOEL, oral, Rat, 1000 mg/kg bw/day

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
in vitro, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
NOAEL, oral, Rat, 225 mg/kg bw/day, no adverse effect observed

- Development

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
NOAEL, oral, Rat, 225 mg/kg bw/day, no adverse effect observed

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard

Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.



SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0

Page 10 / 15

11.2 Information on other hazards

- | | |
|---|---|
| 11.2.1 Endocrine disrupting properties | Contains no ingredients with endocrine-disrupting properties. |
| 11.2.2 Other information | none |

SECTION 12: Ecological information

12.1 Toxicity

Ecological data of complete product are not available.

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Invertebrates, 100 mg/L
EL50, (72h), Algae, 100 mg/L
NOELR, (21d), Invertebrates, 4.45 mg/L
NOELR, (33d), Fish, 10 mg/L
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EC50, (48h), > 10000 mg/l (Gammarus pulex), OECD 202
EC50, (72h), Algae, > 100 mg/l
NOEC, (72h), Pseudokirchneriella subcapitata, ≥ 100 mg/l, OECD 201
NOEC, (21d), Daphnia magna, 10 mg/l, OECD 211
LL50, (96h), Fish, > 100 mg/l, OECD 203
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), Fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
EC50, (48h), Daphnia magna, 5,4 mg/l (OECD 202)
EC50, (72h), Selenastrum capricornutum, 2,1 mg/l
EC50, (3h), Activated sludge, >10000 mg/l
IC50, (21d), Daphnia magna, >0,8 mg/l
LL50, (96h), Oncorhynchus mykiss, 4,5 mg/l
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LC50, (96h), Cyprinus carpio, >100 mg/l
EC50, (24h), Daphnia magna, >100 mg/l
EC50, (72h), Pseudokirchneriella subcapitata, >100 mg/l
NOEC, (72h), Pseudokirchneriella subcapitata, 100 mg/l
NOELR, (24h), Daphnia magna, >100 mg/l
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
NOELR, (14d), Fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated, CAS: 163149-28-8
EC50, (16h), Microorganisms, 10 g/L
NOEC, (28d), Microorganisms, 2 mg/L
NOEC, (14d), Microorganisms, 23,4 - 23,5 mg/L
NOEC, (3h), Microorganisms, 1 g/L
NOEC, (0,5h), Microorganisms, 1 g/L
1-Dodecene, polymer with 1-decene, hydrogenated, CAS: 151006-60-9
EC50, (16h), Microorganisms, 10 g/L
EL50, (48h), Invertebrates, 1 g/L
EL50, (96h), Algae, 1 g/L
NOEC, (28d), Microorganisms, 2 mg/L
NOEC, (14d), Microorganisms, 23,4 - 23,5 mg/L
NOEC, (3h), Microorganisms, 1 g/L

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0

Page 12 / 15

NOEC, (0,5h), Microorganisms, 1 g/L
NOELR, (96h), Fish, 1 g/L
NOELR, (48h), Invertebrates, 1 g/L
NOELR, (96h), Algae, 1 g/L
LL50, (96h), Fish, 1 g/L

12.2 Persistence and degradability

No information available.

Behaviour in environment compartments

Behaviour in sewage plant not determined

Biological degradability not determined

Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 (28d), 31 %, OECD 301 F, The product is not readily biodegradable.
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9 (28d), 2 - 4 %, OECD 301 B, The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended) 130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0

Page 13 / 15

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0 Page 14 / 15

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances $\geq 0.1\%$ that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains $\geq 0.1\%$ of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is subject to the following restrictions. 3
TRANSPORT-REGULATIONS	ADR (2025); IMDG-Code (2025, 42. Amdt.); IATA-DGR (2025)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for young people.
- VOC (2010/75/CE)	0 %

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H411 Toxic to aquatic life with long lasting effects.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H413 May cause long lasting harmful effects to aquatic life.

H317 May cause an allergic skin reaction.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 20.02.2025, Revision 20.02.2025

Version 8.0. Supersedes version: 7.0 Page 15 / 15

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Sens. 1: H317 May cause an allergic skin reaction. ()

Modified position

8.2, 9.1, 11.1, 11.2